



**PRO
TECH**

FREE-SPRAY SANDBLASTING MACHINES

MOD. SC-SCX

Pneumatically operated remote control sandblasting machines, they are supplied equipped with aluminium handle-valve with security, locking system and m.20 (m.5 for Mod. SCX24 and m.10 for Mod. SC24 - SCX60 – SCX120 – SCX200) of sheathed double hose for remote control. Sandblasting machines Mod. SC220 and SC280 are equipped with abrasive metering valve mod. PRV. This valve is adjusted by hand wheel system and controlled by a pneumatic impulse, which determines when is opened or closed in line with the starting and stopping of the working cycle. The range SCX, fitted out with tanks of litres 24-60-120-200, is also available complete with blast hose, nozzle and sandblasting mask.

SC-SCX

Pneumatically operated remote control sanders

Part. Number	Model	Part. Number	Model	Capacity	Project pressure	Dimensions		
						Height	O.D.	Weight
40602400	SC 24	40502400	SCX 24	Lt. 24	8,4 bar	785 mm	315 mm	43 Kg.
40606000	SC 60	40506000	SCX 60	Lt. 60	7,84 bar	995 mm	450 mm	76 Kg.
40612000	SC 120	40512000	SCX 120	Lt. 120	7,84 bar	1225 mm	510 mm	100 Kg.
40620000	SC 200	40520000	SCX 200	Lt. 200	7,84 bar	1385 mm	600 mm	130 Kg.
40622000	SC 220	---	---	Lt. 220	11,76 bar	1500 mm	600 mm	150 Kg.
40628000	SC 280	---	---	Lt. 280	10,50 bar	1615 mm	640 mm	190 Kg.

MACHINES FOR RESTORATION

The sanders for restoration are equipped with remote control and with a sophisticated system for working pressure and abrasive or inert regulation. The machines for restoration are designed for working at pressure from 0,5 to 8 bar, using inerts or abrasive with also the finest sizes. If you need the specific technical details, please ask for the complete catalogue.

Part. Number	Model	Capacity	Project pressure	Dimensions	Weight
45002400	softclean SMS24VR Micrajjet	Lt. 24	8,4 bar	850 x 610 x H = 1280 mm	75 Kg.
40500800	8	Lt. 8	8,8 bar	520 x 625 x H = 1100 mm	29 Kg.
40500900	Micrajjet 8 VR	Lt. 8	8,8 bar	520 x 625 x H = 1100 mm	30 Kg.

SM

Manual sanders

MOD. SM-SMS MOD.SME-SMES Patented sanders equipped with dual pneumatic or electric remote control, to measure. This range of sanders is prearranged for applying several kits to improve their performances. Ask for the full catalogue containing the technical specifications and list of accessories.



Mod. SC



Mod. SCX complete



Mod. MICRAJET 8 VR



Mod. SMS