



PISTON PRESSURE REDUCERS

RPST 12

	1/2" bottom connection 2 1/4" mini ball valves	41011391	a m
	1/2" bottom connection 2 EURO quick couplers	41011351	
RPST 12 PRESSURE REDUCER This is the economic version of the 1/2"	1/2" bottom connection 2 needle valves 1/4" OT	41011341	46, 18, 10 22, 12 22, 12 24, 1
reducer; contrary of PU/4 it has a plastic piston mouvement instead of the diaphragme.	1/2" bottom connection without taps	41011311	PANCER
	1/2" bottom connection without taps and gauge	41011301	

RPST 38

	3/8" bottom connection 2 1/4" mini ball valves	41023551
	3/8" bottom connection 2 EURO quick couplers	41023541
RPST 38 PRESSURE REDUCER This is the smaller version than 1/2" type, similar to the MIGNON it is different for the piston mouvement.	3/8" bottom connection 2 needle valves 1/4" OT	41023531
	3/8" bottom connection without taps	41023511
	3/8" bottom connection without taps and gauge	41023501



RPA 1

	1 1/4" mini ball valve	41035551
	1 EURO quick coupler	41035541
RPA 1 PRESSURE REDUCER	1 needle valve 1/4" OT	41035531
It is the cheapest version of reducer for the small compressors; the knob rotation pushs directly the coil operating on the plastic piston. Lateral 1/4" thread.	Without tap	41035511
	Without tap and gauge	41035501





D=GHCB DF 9GGI F 9 F 98I 7 9F G

MICRO R

MICROMATIC R



HMD9 HMD9 IN 1/4" IN 1/4" AR BR 1/4" GAUGE GAUGE 1/4" OUT 1/4" OUT Pt/min. MICRO R 500 400. 300. 200 100 2 2,5 3 3,5 4 45 5

RATE OF FLOW CURVE MICRO R REDUCERS

The curve points on the abscisses the pressure that the reducer deliverys when the taps are opened and on the ordinates points the rate of flow in I/min.

The curve valves shows the pressure when the reducer is closed.

D=GHCB DF 9GGI F 9 F 98I 79F G

MICRO R

Model AR - 1	1/4" mini ball valveÁ	41034192

Model AR - 1 EURO quick couplerÁ 41034092

MICRO R PRESSURE REDUCER

This is the smallest unit in the series. It is made in metal (casting) and plastics (cup and adjustment knob) that can be locked at the desired operating pressure and has no filter. This type "R" has a plasto piston sliding inside the body. The standard version is fitted with a mini ball valve 1/4" or quick coupler. The pressure gauge dia. 40 mm has a 1/4" connection and a 0-12 BAR scale and PSI scale.

Two models A - B are available, as for diagram at picture in the previous page.

Model AR - without taps out 1/4"A 41034022

Model AR - without taps 1/4" and gauge 1/8" 41034012

age. Model BR - 1 1/4" mini ball valve\(\hat{A}\) 41034792

Model BR - 1 EURO quick couplerÁ 41034772

Model BR - without tap out 1/4" 41034722

Model BR - without taps 1/4" and gauge 1/8" 41034712

9 p 10



MICROMATIC R

1 1/4" mini ball valve 4	1	0)(3	5	1	()	4
--------------------------	---	---	----	---	---	---	---	---	---

1 EURO quick coupler 41035022

MICROMATIC R PRESSURE REDUCER

Similar to the MICRO has a adjustment brought about by a quadruple screw that makes to read the pressure of reducer with one round on 360° on a branded scale under the cup without using the gauge.

without taps out 1/4" 41035002

